Specifications		R-7D
LCD	Size	7″
	Resolution	1920 x 1200 (16:10)
	Pixel Pitch	0.07875(W) x 0.07875(H) mm
	Color Depth	16.7M Colors
	Viewing Angle (Typ.)	160°(H) / 160°(V)
	Luminance of white	500cd/m2
	Contrast Ratio	1200 : 1
	Display Area	151.2(H) x 94.5(V) mm
Input	1 X BNC	12G-SDI
	1 X BNC	3G-SDI
	1 X HDMI	HDMI
Output	1 X BNC	12G-SDI
	1 X BNC	3G-SDI
Input Signal	12G-SDI	11.88Gb/s
	6G-SDI	5.94Gb/s
	3G-SDI	2.970Gbps
	HD-SDI	1.485Gbps
	SD-SDI	270 Mbps
	HDMI	480i / 480p / 576i / 576p / 720p / 1080i / 1080p /2160p
SDI Input Signal Formats	SMPTE ST 2082	2160p (60/59.94/50)
	SMPTE ST 2081	2160p (30/29.97/25/24/23.98)
	SMPTE-425M-A/B	1080p (60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
		1080i (60/59.94/50)
	SMPTE-ST-274M	1080i (60/59.94/50)
		1080p (30/29.97/25/24/24sF/23.98/23.98sF)
	SMPTE ST-296M	720p (60/59.94/50)
	SMPTE ST-260M	1035i (60/59.94)
	SMPTE ST-125M	480i (59.94)
	ITU-R BT.656	576i (50)
Remote Control & Update	LAN	1 x RJ-45 Input(Ethernet)[1] / Control by TVLogic Protocol
	REMOTE	1 x RJ-45 Input / GPI Control
	RS-422	1 x RJ-45 Input / Control by TVLogic or TSL Protocol
	USB	1 x USB A type / Firmware Upgrade
Audio	Audio In	Embedded Audio
	Audio Out	Internal Speaker(Stereo), Analog Stereo (Phone Jack)
General	Power	DC 12V / 2.3A
	Power Consumption (Approx.)	22W
	Operating Temperature	-20 °C to 40 °C (-4 °F to 104 °F)
	Storage Temperature	-30 °C to 50 °C (-22 °F to 122 °F)
Dimensions & Weight	Main Body	430 x 132 x 50.5 (mm) / 16.93 x 4.72 x 1.99 (inch)
	With Rack Ears	480.8 x 132 x 73 (mm) / 18.92 x 5.19 x 2.87 (inch)
	Shipping Box	560 x 240 x 160 (mm) / 22.04 x 9.44 x 6.29 (inch)
	Weight (with Rack Ears)	2.46kg / 5.42lbs
Accessories	Basic Accessories	AC Power Cord, DC Power Adaptor

*The specifications above may be changed without notice.
* When using a DC Adapter other than the one supplied by the manufacturer, please be advised that the adapter with DC 12V/3A ~ 6A can be compatible with the monitor.

[NOTE]
1) If the full model number is R-7D-A1, the LAN Input is supported.
If the full model number is R-7D, the monitor has the RS-422 Output port instead of the LAN Input port.
The full model number can be checked on the rear label.