

Specifications		LUM-096G
LCD	Size	10.1"
	Resolution	1920 x 1200 (16:10)
	Pixel Pitch	0.1122(H) x 0.1128(V) mm
	Color Depth	16.7M Colors
	Viewing Angle	170°(H) / 170°(V)
	Luminance of white	1000 cd/m ²
	Contrast	1000 : 1
	Display Area	216.58(H) x 135.36(V) mm
Input & Output	SDI-A	12G/6G/3G/HD-SDI Input
	SDI-B	3G/HD/SD-SDI Input
	SDI-C	3G/HD-SDI Input (For Quad-Link 4K/UHD Input only) or 12G/6G/3G/HD-SDI Output (Passive Through Out)
	SDI-D	3G/HD-SDI Input (For Quad-Link 4K/UHD Input only) or 3G/HD/SD-SDI Output (Passive Through Out)
	1 x HDMI	HDMI 2.0
Input Signal	12G-SDI	12Gb/s
	6G-SDI	6Gb/s
	3G-SDI	2.970Gb/s
	HD-SDI	1.485Gb/s
	SD-SDI	270Mbps
	HDMI	480i / 480p / 576i / 576p / 720p / 1080i / 1080p / 2160p
SDI Input Signal Formats	SMPTE ST-2082	2160p (60/59.94/50) ¹⁾
	SMPTE ST-2081	2160p (30/29.97/25/24/23.98) ¹⁾
	SMPTE ST-425M-A/B	1080p (60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
		1080i (60/59.94/50)
	SMPTE ST-274M	1080i (60/59.94/50)
		1080p (30/29.97/25/24/24sF/23.98/23.98sF)
	SMPTE ST-296M	720p (60/59.94/50)
	SMPTE ST-260M	1035i (60/59.94)
SMPTE ST-125M	480i (59.94)	
ITU-R BT.656	576i (50)	
Remote Control & Update	1 x REMOTE	RJ-45 Input, GPI Control
	2 x RS-422	RJ-45 Input & Output, Control by TVLogic Protocol
	1 x USB	USB A type, Firmware Upgrade
Audio In	Embedded Audio / Analog Stereo (Phone Jack)	
Audio Out	Internal Speaker(Stereo) / Analog Stereo (Phone Jack)	
Power	12V DC/24V DC	
Power Consumption (Approx.)	30 Watts(DC)/Max 2.4A	
Operating Temperature	-20 °C to 40 °C (-4 °F to 104 °F)	
Storage Temperature	-30 °C to 50 °C (-22 °F to 122 °F)	
Dimensions	Main Body	254 x 175 x 60 mm / 1.00 x 6.89 x 2.36 inch
	With Stand	295.2 x 194.2 x 90 mm / 11.62 x 7.65 x 3.54 inch
	Shipping Box	330 x 180 x 250 mm / 12.99 x 7.09 x 9.84 inch
Weight (with stand)	2.44Kg / 5.38lb	
Basic Accessories	AC Power Cord, DC Power adaptor, Stand, Tap Bolt	
Optional Accessories	Acrylic Protector, Sun Hood	